

SNF (UK) Limited - Solutions House, Ripley Close, Normanton Industrial Estate, Normanton WF61TB - England, UK

Phone: 01924-311000 [e-mail: technical@snf.co.uk](mailto:technical@snf.co.uk)

PRODUCT INFORMATION SHEET FLOFOAM 139F

CHEMICAL TYPE:

BLEND OF HYDROCARBONS, FATTY ACID ESTERS AND SURFACTANTS.

IONIC CHARGE:

NON IONIC.

PHYSICAL SPECIFICATION

1. APPEARANCE

AMBER LIQUID.

2. WATER MISCIBILITY:

FORMS A GOOD DISPERSION IN WATER.

3. FLUIDITY:

VISCOSITY NOT GREATER THAN 1000cPs @ 20°C. DIN 53019 100RPM.

4. CLEANLINESS

NO PARTICLES AFTER SCREENING THROUGH A 400-MICRON APERTURE SCREEN.

PURPOSE:

Flofoam 139F is particularly effective in effluent / sewage plants. It is effective over a wide pH range and operates well in the presence of anionic, non-ionic and cationic surfactants.

Dosage rate may vary according to conditions and should be determined by trial.

STORAGE:

Store in closed containers. Avoid extremes of temperature.

STABILITY:

12 months minimum shelf life when stored at normal temperature.

PACKAGING:

200 litre or 1000 litre plastic containers.